arXiv:1204.3840v1 [quant-ph] 17 Apr 2012

Classical communication and non-classical fidelity of quantum teleportation

Manik Banik[*] and MD. Rajjak Gazi[†]
Physics and applied mathematics unit, Indian statistical unit, 203 B.T. Road, Kolkata-700108, India

In quantum teleportation, the role of entanglement has been much discussed. It is known that entanglement is necessary for achieving non-classical teleportation fidelity. Here we focus on the amount of classical communication that is necessary to obtain non-classical fidelity in teleportation. We quantify the amount of classical communication that is sufficient for two one-bit and one two-bits noisy classical channels for non-classical fidelity and we also find the necessary amount of classical communication for isotropic transformation.

PACS numbers: 03.67.Hk, 03.67.-a, 03.65.Aa

I. INTRODUCTION

Quantum information theory, the generalization of classical information theory governing by the rules of quantum mechanics has been a subject of much recent interest. It is now known that various interesting phenomena including teleportation [1–3] and dense coding [4] can occur when the laws of quantum mechanics are invoked in information processing. It was customary to ignore the classical communication cost in quantum information processing. The motivation was that classical communication is free whereas quantum communication and entanglement are expensive. However, as emphasized in [5], in applications such as dense coding, classical communication cost is of primary interest.

Teleportation is an interesting quantum information process, where an unknown quantum state can be transferred between two spatially separated parties. Bennett et al. [1] have shown that this seemingly impossible task can be done in quantum mechanical framework, which is known as quantum teleportation. With the help of two different kinds of resources; 2-cbits of classical communication and 1-ebit entanglement, the unknown qubit state $|\phi\rangle$ can be transferred from Alice to Bob with perfect accuracy. If degree of entanglement is weakened then how the teleportation fidelity behaves is discussed in literature [6, 7]. We also know that 2-cbits of communication is necessary for exact teleportation.

If any of the resources (i.e. classical communication as well as quantum correlation) are not used then the teleportation fidelity is $\frac{1}{2}$. If only classical communication is allowed between Alice and Bob then they can raise the fidelity up to $\frac{2}{3}$ and this value is optimal [8–10]. This value is sometime called classical fidelity of teleportation process. If in any teleportation scheme the value of the teleportation fidelity is greater than $\frac{2}{3}$ we say the teleportation process is non-classical or quantum, in other words some quantum correlation must have been used in the process. When 2-classical bits and 1-ebit is used in teleportation protocol the value of teleportation fidelity 1 reflects the complete accuracy of the process. If the degree of entanglement used in the teleportation process be weakened in the form of Werner state $W_\alpha = \alpha|\psi^{singlet}\rangle\langle\psi^{singlet}| + (1-\alpha)\frac{I}{2}\otimes\frac{I}{2}$, then teleportation fidelity (say f) takes the value $f = \frac{1+\alpha}{2}$ [6], from which we infer that to achieve the non-classical fidelity the Werner state has to be necessarily entangled. Interestingly it has been shown that any two qubits entangled state is good for non-classical teleportation [11].

In this paper we pose the following question; what is the necessary amount of classical communication so that teleportation fidelity is non-classical without any restriction on shared entanglement? We have studied two cases; in one case we have considered two single-bit noisy classical channels and in other case we have considered one two-bits noisy classical channel. We have shown that in the first case $(0.255+\epsilon)$-bits classical communication (with $\epsilon > 0$) is sufficient to make the teleportation fidelity non-classical. In the second case, $(0.208+\epsilon)$-bits classical communication is sufficient. We also argue that $(0.208+\epsilon)$-bits classical communication is necessary if the quantum state transforms isotropically in the teleportation.

II. TELEPORTATION PROTOCOL USING TWO 1-BIT NOISY CLASSICAL CHANNELS

Suppose Alice has to teleport an unknown qubit state $|\phi_1\rangle = a|0_1\rangle + b|1_1\rangle$ to Bob. They have a shared singlet pair $|\psi^-_{23}\rangle = \frac{|0_2 1_3\rangle - |1_2 0_3\rangle}{\sqrt{2}}$ i.e. they are allowed to share 1-ebit entanglement as teleportation resource, and they have two noisy channel C_η and C_δ. The noisy classical channel C_z $(z \equiv \eta, \delta)$ is characterized by the conditional probability :-

$$\begin{aligned} p(a|a) &= z \\ p(\bar{a}|a) &= 1-z \end{aligned} \tag{1}$$

where a is Alice's input bit and $a \in \{0,1\}$; $\bar{a}$ denote complement bit of a. The value of z lies between $\frac{1}{2}$ and 1. The amount of classical communication is quantified [12, 13] as mutual information between Alice's input and

---

[*] Electronic address: manik11ju@gmail.com
[†] Electronic address: rajjak˙r@isical.ac.in

Bob's output, which is in this case :-

$$C_z := 1 - H(z) \tag{2}$$

where $H(z)$ be the Shannon entropy.

The teleportation protocol goes as standard teleportation protocol [1] : Alice first performs measurement on the joint system of unknown qubit and her part of the entangled pair in Bell basis ($|\psi^{\pm}\rangle, |\varphi^{\pm}\rangle$), Where

$$|\psi^{\pm}\rangle = \frac{|01\rangle \pm |10\rangle}{\sqrt{2}} \quad ; \quad |\varphi^{\pm}\rangle = \frac{|00\rangle \pm |11\rangle}{\sqrt{2}} \tag{3}$$

After the measurement Alice sends the results to Bob by using the two noisy classical channel. Bob, after receiving the classical bits, performs the unitary operation as required for perfect teleportation. This will result the following density matrix for Bob's qubit;

$$\begin{aligned}\varrho' = \eta\delta\varrho + \eta(1-\delta)\sigma_z\varrho\sigma_z + \delta(1-\eta)\sigma_x\varrho\sigma_x \\ + (1-\eta)(1-\delta)\sigma_y\varrho\sigma_y\end{aligned} \tag{4}$$

The measure of success is given by the quantity $\langle\phi_1|\varrho'|\phi_1\rangle$. The average of this quantity over all possible states gives us the fidelity of the teleportation process [6]. For a qubit system the density matrix ϱ can be written as $\frac{1}{2}(1 + \vec{n}.\sigma)$ where $\vec{n}(= (n_x, n_y, n_z) = (sin\theta cos\phi, sin\theta sin\phi, cos\theta))$ is unit vector on Poincare sphere. Therefore the fidelity of the teleportation process is the following;

$$\begin{aligned}f = \langle Tr[\varrho(\eta\delta\varrho + \eta(1-\delta)\sigma_z\varrho\sigma_z + \delta(1-\eta)\sigma_x\varrho\sigma_x + \\ (1-\eta)(1-\delta)\sigma_y\varrho\sigma_y)]\rangle\end{aligned}$$

$$f = \frac{1 + 2\eta\delta}{3} \tag{5}$$

In the process of teleportation process described above, the total classical communication used amounts to sum of the capacity (mutual information) of the two independent noisy classical channel i.e. $[2 - H(\eta) - H(\delta)]$-bits. The fidelity of the teleportation will go beyond the classical limit $(i.e. f > \frac{2}{3})$ if we have $\eta\delta > \frac{1}{2}$. With the restriction $\eta\delta > \frac{1}{2}$ on the parameter η and δ, the minimum of the classical cost is found when $\eta = \delta = \frac{1}{\sqrt{2}}$. The optimal communication has been found to be $[2 - H(\eta) - H(\delta)] \approx 0.255$-bits. Thus we can say that $(0.255 + \epsilon)$-bits classical communication with $\epsilon > 0$, is sufficient for achieving non-classical fidelity in the teleportation process when two independent noisy classical channels have been used.

III. TELEPORTATION PROTOCOL USING ONE 2-BIT NOISY CLASSICAL CHANNEL

Let Alice and Bob are sharing a 2-bit noisy classical channel which is characterized by following conditional probability :-

$$\begin{aligned}P(ab|ab) &= p_1 \\ P(\bar{a}b|ab) &= p_2 \\ P(a\bar{b}|ab) &= p_3 \\ P(\bar{a}\bar{b}|ab) &= p_4\end{aligned} \tag{6}$$

where ab etc. are Alice's two inputs and take values from the set $\{00, 01, 10, 11\}$ and $p_i \geq 0$ for $i = 1, 2, 3, 4$ and $\Sigma_i p_i = 1$. The amount of classical communication can be quantified as mutual information between Alice's input variables X and Bob's outputs variables Y

$$\begin{aligned}I(X:Y) &= H(X) + H(Y) - H(X,Y) \\ &= 2 + \Sigma_{i=1}^{4}\, p_i log(p_i)\end{aligned} \tag{7}$$

From the definition it is clear that at the two extreme cases, (i) one of $p_i = 1$ and (ii) all p_i's are equal, we have amount of communication 2 bit and 0 bit respectively.
If Alice and Bob follows the same teleportaion protocol as before, using the 2-bit noisy classical channel, the resulting density matrix for Bob's qubit is as follows;

$$\varrho' = p_1\varrho + p_2\sigma_x\varrho\sigma_x + p_3\sigma_z\varrho\sigma_z + p_4\sigma_y\varrho\sigma_y \tag{8}$$

The teleportation fidelity in this case becomes,

$$\begin{aligned}f &= \langle Tr[\varrho(p_1\varrho + p_2\sigma_x\varrho\sigma_x + p_3\sigma_z\varrho\sigma_z + p_4\sigma_y\varrho\sigma_y)]\rangle \\ &= p_1 + \frac{1}{3}(p_2 + p_3 + p_4) \\ &= \frac{1 + 2p_1}{3}\end{aligned} \tag{9}$$

The amount of classical bits used in this process is

$$C = I(X:Y) = 2 + \Sigma_{i=1}^{4} p_i log(p_i) \tag{10}$$

From Eqn.(9) it is clear that we will get non classical fidelity (i.e. $f > \frac{2}{3}$) if we have $p_1 > \frac{1}{2}$. With this restriction on p_1 we want to find the minimum amount of classical communication C. From the expression of C it can be shown that the minimum will be achieved when $p_2 = p_3 = p_4$. Thus we have :-

$$C = 2 + p_1 log p_1 + (1 - p_1) log(\frac{1 - p_1}{3}) \tag{11}$$

In the range $\frac{1}{2} \leq p_1 \leq 1$, C is a monotonic increasing function of p_1 and the value of C at $p_1 = \frac{1}{2}$ is $C_{\frac{1}{2}} \approx 0.208$. Therefore we can say that $(0.208 + \epsilon)$-bits classical communication ($\epsilon > 0$) is sufficient to get non classical teleportation fidelity.
Now it is interesting to note that we are getting the optimal value of classical cost when $p_2 = p_3 = p_4$ and in this case the final density matrix is given by $\frac{1}{2}[1 + (2f - 1)\vec{n}.\sigma]$, where $f = \frac{2p_1+1}{3}$; which means that the optimality is achieved when the state transform isotropically.

IV. $(0.208+\epsilon)$ BITS ARE NECESSARY FOR QUANTUM FIDELITY WHERE STATE TRANSFORMS ISOTROPICALLY

Now we will show that 0.208-bits classical communication is necessary to obtain non classical fidelity of the teleportation process which transform the state isotropically. To prove this, we assume there is a teleportation process which transform the state isotropically but at the same time attain non-classical fidelity by using $(0.208-\epsilon)$-bits of classical communications. Let Alice and Bob share a singlet state and Alice in order to send two bits of classical information, applies the unitary transformation accordingly as is done in the standard dense coding protocol [4]. Then Alice teleport the qubit to Bob by the teleportation channel with non-classical fidelity which use $(0.208-\epsilon)$-bits of classical communications and transform the state isotropically.
Depending on the Alice's classical bits, the possible two qubits density matrix on Bob's side are as follows:-

$$\rho_i = \frac{(1-p_1)}{3}\mathbf{1} + \frac{(4p_1-1)}{3}\sigma_i|\psi^-\rangle\langle\psi^-|\sigma_i \qquad (12)$$

where $i = 0, x, y, z$ and $\sigma_0 = \mathbf{1}$. The amount of classical bits that can be extracted [14, 15] from this ensemble is bounded by the Holevo quantity χ [16] which in this case, is given by

$$\chi = 2 + p_1 log p_1 + (1-p_1) log(\frac{1-p_1}{3}) \qquad (13)$$

and χ is $(0.208+\epsilon)$ for non-classical fidelity. Interestingly, this bound can be achieved by making measurement on two qubits in the Bell basis and extracts classical information as is done in super dense coding [4]. But this implies that by communicating $(0.208-\epsilon)$-bits information, one can generate $(0.208+\epsilon)$-bits, which violates causality principle. This proves that $(0.208+\epsilon)$ bits are necessary for teleportation which is isotropic and achieves quantum fidelity.

V. DISCUSSION

The optimal amount of classical communication that is necessary for achieving non-classical fidelity in quantum teleportation still remains an open problem. We only provide sufficient amount in two cases. It is interesting that with further restriction on state transformation, we find the necessary amount of classical communication to reach quantum fidelity.

Acknowledgment

We like to thank G.Kar for many simulating discussion and giving suggestions regarding the use of two-bits noisy classical channel. We also like to acknowledge S.Ghosh, S.Bandyopadhyay, S.Kunkri, A.Rai and S.Das for many helpful discussions.

---

[1] C. H. Bennett et al., Phys. Rev. Lett. 70, 1895 (1993).
[2] M. Riebe et al., Nature 429, 734-737 (17 June 2004)
[3] A. Furusawa, Science, Vol. 282 no. 5389 pp. 706-709 (1998).
[4] C. H. Bennett and S. J. Wiesner, Phys. Rev. Lett. 69,2881 (1992).
[5] H.-K. Lo and S. Popescu, Phys. Rev. Lett. 83, 1459(1999).
[6] S. Popescu, Phys. Rev. Lett. 72, 797 (1994).
[7] M. Horodecki et al., Phys. Rev. A 60,1888 (1999).
[8] T. Mor, P. Horodecki, arXiv:quant-ph, 9906039(v1) (1999).
[9] L. Henderson et al.,Phys. Rev. A, 61, 062306 (2000).
[10] S. Massar and S. Popescu, Phys. Rev. Lett. 74, 1259 (1995).
[11] F.Verstraete and H.Verschelde, Phys. Rev. Lett.90,097901(2003).
[12] G. Kar, J. Phys. A: Math. Theor. 44 (2011) 152002.
[13] M.J.W. Hall, Phys. Rev. A , 84, 022102 (2011).
[14] Mark M. Wilde, "From Classical to Quantum Shannon Theory", arXiv:1106.1445.
[15] A.Nielsen and I.L.Chuang,Quantum Computation and Quantum Information.
[16] Alexander S. Holevo. Bounds for the quantity of information transmitted by a quantum communication channel. Problems of Information Transmission, 9:177-183, 1973.